

PRODUCT INFORMATION

F-135

DESCRIPTION

High tensile mono-directional fibre glass reinforced single sided tape.

PRODUCT DATA

Backing	Glass fibre reinforced + BOPP film
Adhesive	Synthetic rubber and resins

	Unit	Value	Method
Total thickness	mm	0.148	PSTC 133
Adhesion to steel	N/25mm	20	PSTC 101
Tensile strength MD	N/25mm	1250	PSTC 131
Elongation at break	%	4.5	PSTC 131
Temp. Resistance	°C	60°C	=

APPLICATION

High tensile mono-directional reinforced tape suitable for bundling and carton reinforcement, specifically for heavy articles.

Features	Benefits	
Synthetic rubber and resins adhesive	✓ High adhesion in most situations	✓ Excellent application results on different surfaces
Mono-directional glass fibre reinforced backing	✓ High resistance to break ✓ Easy handling	✓ High security in application

CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperature are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.