

PRODUCT INFORMATION

M-400

DESCRIPTION

Masking tape for industrial building applications; easily removable, even from delicate surfaces.

PRODUCT DATA

Backing	58 g/m ² natural saturated paper; white
Adhesive	Natural rubber and resins solvent based

	Unit	Value	Method
Total thickness	mm	0.120	PSTC 133
Adhesion to steel	N/25mm	5	PSTC 101
Tensile strength MD	N/25mm	82	PSTC 131
Elongation at break	%	7	PSTC 131
Temp. Resistance	°C	60°C (1 hour)	=

APPLICATION

Masking tape recommended for professional use in painting and building. Recommended to remove within 60 hours.

Features	Benefits	
Natural rubber and resins solvent based adhesive	✓ Well balanced adhesion even on irregular surfaces	✓ Easy removal without adhesive residue
Saturated paper backing	✓ Well adaptable to most surfaces ✓ Removable without breaking ✓ Hand tearable	✓ Compatible with most common paints and lacquers

CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperatures are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.