

PRODUCT INFORMATION

M-410

DESCRIPTION

Masking tape for wall-painting on building sites.

PRODUCT DATA

Backing	72 g/m ² natural saturated crepe paper; white
Adhesive	Natural rubber and resins solvent based

	Unit	Value	Method
Total thickness	mm	0.136	PSTC 133
Adhesion to steel	N/25mm	4.8	PSTC 101
Tensile strength MD	N/25mm	100	PSTC 131
Elongation at break	%	8	PSTC 131
Temp. Resistance	°C	80°C (30 min)	=

APPLICATION

Masking tape suitable for wall-painting on building and construction sites, and industrial applications when temperature does not exceed 80°C. Recommended to remove within 48 hours.

Features	Benefits	
Natural rubber and resins solvent based adhesive	✓ Easy removal without adhesive residue ✓ Heat resistant up to 80°C (30 min)	✓ Good adhesion even on irregular surfaces
Saturated paper backing	✓ Higher thickness ✓ Well conformable to most shaped surfaces ✓ Hand tearable	✓ Compatible with most common paints and lacquers ✓ Removable without breaking

CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperatures are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.