

PRODUCT INFORMATION

M-420

DESCRIPTION

Economical version general purpose masking tape.

PRODUCT DATA

Backing	58 g/m ² natural saturated crepe paper; white
Adhesive	Synthetic rubber and resins

	Unit	Value	Method
Total thickness	mm	0.108	PSTC 133
Adhesion to steel	N/25mm	7.5	PSTC 101
Tensile strength MD	N/25mm	85	PSTC 131
Elongation at break	%	8	PSTC 131
Temp. Resistance	°C	50°C	=

APPLICATION

Economical masking tape, suitable for all kinds of simple jobs and DIY applications. Tape must be used at room temperature. Recommended to remove within 24 hours.

Features	Benefits	
Synthetic rubber and resins	✓ Easy removal without adhesive residue	✓ Good adhesion
Saturated paper backing	✓ Compatible with most common paints and lacquers ✓ Hand tearable	✓ Good conformability ✓ Removable without breaking

CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperature are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.