

PRODUCT INFORMATION

M-500

DESCRIPTION

Paper masking tape.

PRODUCT DATA

Backing	80 g/m ² saturated crepe paper; beige
Adhesive	Natural rubber and resins based

	Unit	Value	Method
Total thickness	mm	0.153	PSTC 133
Adhesion to steel	N/25mm	7	PSTC 101
Tensile strength MD	N/25mm	110	PSTC 131
Elongation at break	%	10	PSTC 131
Temp. Resistance	°C	80°C (30 min)	=

APPLICATION

Premium masking tape, suitable for professional painters in the construction industry, car refinishing and for other industrial applications. With a strong paper backing for better resistance even in heavy use such as building, construction and industrial applications. Recommended to remove within 48 hours.

Features	Benefits	
Natural rubber and resins based adhesive	✓ Good adhesion on irregular surfaces	✓ Easy removal without adhesive residue
Saturated crepe paper backing	✓ Well conformable to most shaped surfaces ✓ High mechanical resistance	✓ Compatible with most common paints and lacquers ✓ Hand tearable

CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperatures are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Sica's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.