

# PRODUCT INFORMATION

## M-50Y

### DESCRIPTION

Waterproof yellow masking tape.

### PRODUCT DATA

<b>Backing</b>	63 g/m <sup>2</sup> waterproof saturated crepe paper; lemon yellow
<b>Adhesive</b>	Natural rubber and resins solvent based

	<b>Unit</b>	<b>Value</b>	<b>Method</b>
<b>Total thickness</b>	mm	0.130	PSTC 133
<b>Adhesion to steel</b>	N/25mm	4.8	PSTC 101
<b>Tensile strength MD</b>	N/25mm	90	PSTC 131
<b>Elongation at break</b>	%	8	PSTC 131
<b>Temp. Resistance</b>	°C	90°C (30 min)	=

### APPLICATION

Waterproof masking tape widely used for car repair applications as well as for wall-painting on building and construction sites and industrial use.

<b>Features</b>	<b>Benefits</b>	
Natural rubber solvent based adhesive	✓ Good adhesion on uneven surfaces also ✓ Heat resistant up to 90°C (30 min)	✓ Easy removal without adhesive residue, if it is removed as soon as paint is dry
Water resistant saturated paper backing	✓ Well conformable to most shaped surfaces ✓ Highly resistant to moisture and water	✓ Compatible with most common paints and lacquers ✓ Removable without breaking ✓ Hand tearable

### CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperatures are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.