

# PRODUCT INFORMATION

## M-735

### DESCRIPTION

General purpose masking tape.

### PRODUCT DATA

<b>Backing</b>	58 g/m <sup>2</sup> natural saturated crepe paper; white
<b>Adhesive</b>	Natural rubber and resins solvent based

	<b>Unit</b>	<b>Value</b>	<b>Method</b>
<b>Total thickness</b>	mm	0.120	PSTC 133
<b>Adhesion to steel</b>	N/25mm	4	PSTC 101
<b>Tensile strength MD</b>	N/25mm	85	PSTC 131
<b>Elongation at break</b>	%	7.5	PSTC 131
<b>Temp. Resistance</b>	°C	60°C (30 min)	

### APPLICATION

General purpose masking tape, suitable for all kinds of simple painting jobs. Tape must be applied at room temperature. Recommended to remove within 36 hours.

<b>Features</b>	<b>Benefits</b>	
Natural rubber and resins solvent based adhesive	✓ Resistant to most common paints ✓ Easy removal without adhesive residue	✓ Good adhesion even on irregular surfaces
Saturated paper backing	✓ Well conformable to most shapes ✓ Compatible with most common paints and lacquers	✓ Removable without breaking ✓ Hand tearable

### CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperatures are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.