

PRODUCT INFORMATION

M-755M

DESCRIPTION

Masking tape for car repair.

PRODUCT DATA

Backing	58 g/m ² saturated crepe paper; mandarine color
Adhesive	Natural rubber and resins based

	Unit	Value	Method
Total thickness	mm	0.125	PSTC 133
Adhesion to steel	N/25mm	4.3	PSTC 101
Tensile strength MD	N/25mm	85	PSTC 131
Elongation at break	%	8	PSTC 131
Temp. Resistance	°C	80°C (30 min)	=

APPLICATION

Masking tape suitable for car repair applications when temperature does not exceed 80°C.

Features	Benefits	
Natural rubber and resins based adhesive	✓ Good adhesion even on uneven surfaces ✓ Heat resistant up to 80°C (30 min)	✓ Easy removal, if removed as soon as paint is dry, without adhesive residue
Saturated crepe paper backing	✓ Well conformable to most shaped surfaces ✓ Removable without breaking	✓ Compatible with most paints and lacquers ✓ Hand tearable

CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperatures are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Sica's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.