

PRODUCT INFORMATION

M-780+

DESCRIPTION

Waterproof masking tape for car refinishing, construction sights and various industrial applications.

PRODUCT DATA

Backing	74 g/m ² waterproof saturated crepe paper; beige
Adhesive	Natural rubber and resins solvent based

	Unit	Value	Method
Total thickness	mm	0.140	PSTC 133
Adhesion to steel	N/25mm	7.5	PSTC 101
Tensile strength MD	N/25mm	100	PSTC 131
Elongation at break	%	8	PSTC 131
Temp. Resistance	°C	85°C (30 min)	=

APPLICATION

High adhesion waterproof masking tape for car refinishing, also suitable for painting on building and construction sites and for industrial use.

Features	Benefits	
Natural rubber and resins solvent based adhesive	✓ High adhesion on rough surfaces ✓ Heat resistant (85°C - 30 min)	✓ Excellent adhesion to own backing ✓ Removal without adhesive residue
Waterproof saturated paper backing	✓ Well conformable to most shaped surfaces ✓ Removable without tearing	✓ Compatible with most common paints and lacquers ✓ Hand tearable

CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperatures are lower than suggested, it is always required to store the tape at normal temperature before use. This information is given to the best of Sivad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.