

PRODUCT INFORMATION

M-805

DESCRIPTION

Waterproof blue masking tape.

PRODUCT DATA

Backing	63 g/m ² waterproof saturated crepe paper; blue
Adhesive	Natural rubber and resins solvent based

	Unit	Value	Method
Total thickness	mm	0.130	PSTC 133
Adhesion to steel	N/25mm	4.8	PSTC 101
Tensile strength MD	N/25mm	90	PSTC 131
Elongation at break	%	8	PSTC 131
Temp. Resistance	°C	90°C (30 min)	=

APPLICATION

Waterproof masking tape widely used for car repair applications as well as for wall-painting on building and construction sites and industrial use.

Features	Benefits	
Natural rubber solvent based adhesive	✓ Easy removal without adhesive residue, if it is removed as soon as paint is dry	✓ Heat resistant up to 90°C (30 min) ✓ Good adhesion on uneven surfaces also
Water resistant saturated paper backing	✓ Well conformable to most shaped surfaces ✓ Compatible with most common paints and lacquers	✓ Highly resistant to moisture and water ✓ Removable without breaking ✓ Hand tearable

CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperatures are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.