

# PRODUCT INFORMATION

## M-806

### DESCRIPTION

Waterproof masking tape for automotive repair workshops.

### PRODUCT DATA

<b>Backing</b>	78 g/m <sup>2</sup> saturated crepe paper water resistant; brown
<b>Adhesive</b>	Natural rubber and resins solvent based

	<b>Unit</b>	<b>Value</b>	<b>Method</b>
<b>Total thickness</b>	mm	0.140	PSTC 133
<b>Adhesion to steel</b>	N/25mm	5	PSTC 101
<b>Tensile strength MD</b>	N/25mm	100	PSTC 131
<b>Elongation at break</b>	%	8	PSTC 131
<b>Temp. Resistance</b>	°C	100°C (120°C x 30min)	=

### APPLICATION

Waterproof masking tape suitable for use in high performance automotive repair workshops.

<b>Features</b>	<b>Benefits</b>	
Natural rubber and resins solvent based adhesive	<ul style="list-style-type: none"><li>✓ Specific formulation allows to work perfectly even in overlapping and with masking paper/film applied</li><li>✓ Resistant to thinners</li></ul>	<ul style="list-style-type: none"><li>✓ Heat resistant up to 120°C (30 min), suitable for oven drying 100°C cycles</li><li>✓ No adhesive residue after removal from car body, plastics, glass, rubber profiles, etc., even when Infra Red lamps are used</li></ul>
Saturated paper backing	<ul style="list-style-type: none"><li>✓ Excellent performances with traditional solvent based and water based paints</li><li>✓ Good resistance to break</li></ul>	<ul style="list-style-type: none"><li>✓ Well adaptable to different shaped surfaces</li><li>✓ Thank to its waterproof property, suitable for wet sanding</li></ul>

### CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperatures are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Sica's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.