

PRODUCT INFORMATION

M-828

DESCRIPTION

Green waterproof masking tape for automotive repair workshops.

PRODUCT DATA

Backing	92 g/m ² saturated crepe paper water resistant; green
Adhesive	Natural rubber and resins solvent based

	Unit	Value	Method
Total thickness	mm	0.190	PSTC 133
Adhesion to steel	N/25mm	7.25	PSTC 101
Tensile strength MD	N/25mm	110	PSTC 131
Elongation at break	%	13	PSTC 131
Temp. Resistance	°C	100°C x 1h; up to 120°C short period	=

APPLICATION

High performance waterproof masking tape suitable for use in automotive repair applications.

Features	Benefits	
Natural rubber and resins solvent based adhesive	<ul style="list-style-type: none">✓ Specific formulation allows to work perfectly even in overlapping and with masking paper/film applied✓ Resistant to thinners	<ul style="list-style-type: none">✓ Heat resistant up to 120°C (short period), suitable for oven drying 100°C cycles✓ No adhesive residue after removal from car body, plastics, glass, rubber profiles, etc., even when Infra Red lamps are used
Green waterproof saturated paper backing	<ul style="list-style-type: none">✓ Excellent performances with traditional solvent based and water based paints✓ Good resistance to break✓ Highly conformable	<ul style="list-style-type: none">✓ Well adaptable to different shaped surfaces✓ Thank to its waterproof property, suitable for wet sanding✓ Well performing in high moisture conditions

CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperatures are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.