

# PRODUCT INFORMATION

## M-85

### DESCRIPTION

High performance masking tape “solvent free” UV and weather resistant.

### PRODUCT DATA

<b>Backing</b>	74 g/m <sup>2</sup> UV resistant waterproof blue saturated paper
<b>Adhesive</b>	Acrylic water based

	<b>Unit</b>	<b>Value</b>	<b>Method</b>
<b>Total thickness</b>	mm	0.130	PSTC 133
<b>Adhesion to steel</b>	N/25mm	3.75	PSTC 101
<b>Tensile strength MD</b>	N/25mm	100	PSTC 131
<b>Elongation at break</b>	%	8	PSTC 131

### APPLICATION

High performance waterproof and weather resistant blue masking tape recommended for indoor and outdoor applications where surfaces are exposed to UV rays and moisture. Specific for metal, aluminium, wood and glass surfaces.

16 days clean removal outdoor.

<b>Features</b>	<b>Benefits</b>	
Acrylic water based adhesive	<ul style="list-style-type: none"><li>✓ Specific for metal, aluminium, wood and glass</li><li>✓ Easy removal without adhesive residue up to 16 days</li></ul>	<ul style="list-style-type: none"><li>✓ UV and weather resistant</li><li>✓ Easy unwinding</li></ul>
Water resistant saturated paper backing	<ul style="list-style-type: none"><li>✓ Water resistant</li><li>✓ High weight paper suitable for heavy duty applications</li><li>✓ Excellent conformability</li></ul>	<ul style="list-style-type: none"><li>✓ Compatible with most common paints</li><li>✓ Removable without breaking</li><li>✓ Hand tearable</li></ul>

### CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperature are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Sica's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.