

PRODUCT INFORMATION

M-90

DESCRIPTION

Premium masking tape UV and weather resistant.

PRODUCT DATA

Backing	74 g/m ² UV resistant waterproof blue saturated paper
Adhesive	Acrylic solvent based

	Unit	Value	Method
Total thickness	mm	0.130	PSTC 133
Adhesion to steel	N/25mm	4.75	PSTC 101
Tensile strength MD	N/25mm	100	PSTC 131
Elongation at break	%	8	PSTC 131

APPLICATION

Premium waterproof blue masking tape especially recommended for indoor and outdoor applications where surfaces are exposed to UV rays and moisture. Suitable also for shipyard applications.

Specially recommended for metal, aluminium, glass, wood and plastic surfaces.

28 days clean removal outdoor.

Features	Benefits
Acrylic solvent based adhesive	<ul style="list-style-type: none">✓ Recommended for metal, aluminium, glass, wood and plastics✓ Easy removal without adhesive residue up to 28 days✓ UV and weathering resistant✓ Easy unwinding
Water resistant saturated paper backing	<ul style="list-style-type: none">✓ Water resistant✓ High weight paper suitable for heavy duty applications✓ Excellent conformability✓ Compatible with most common paints✓ Removable without breaking✓ Hand tearable

CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperatures are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Sica's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.