

# PRODUCT INFORMATION

## P-1505

### DESCRIPTION

Medium tensile palletizing single sided tape.

### PRODUCT DATA

<b>Backing</b>	0.050 mm MOPP film; white
<b>Adhesive</b>	Natural rubber and resins

	<b>Unit</b>	<b>Value</b>	<b>Method</b>
<b>Total thickness</b>	mm	0.070	PSTC 133
<b>Adhesion to steel</b>	N/25mm	4.3	PSTC 101
<b>Tensile strength MD</b>	N/25mm	350	PSTC 131
<b>Elongation at break</b>	%	33	PSTC 131
<b>Temp. Resistance</b>	°C	60°C	=

### APPLICATION

Medium strength tensilized PP film tape suitable for fixing components inside refrigerators and other household appliances in line production and during transport; removable without any adhesive residue.

<b>Features</b>	<b>Benefits</b>	
Natural rubber and resins adhesive	✓ No chemical reaction with application surfaces ✓ Removable without residues	✓ Good adhesion in most situations
MOPP backing	✓ High resistance at break	✓ High security in application

### CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperature are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.