

PRODUCT INFORMATION

P-1550

DESCRIPTION

Medium tensile palletizing single sided tape.

PRODUCT DATA

Backing	0.055 mm MOPP film; blue
Adhesive	Natural rubber and resins

	Unit	Value	Method
Total thickness	mm	0.076	PSTC 133
Adhesion to steel	N/25mm	4.3	PSTC 101
Tensile strength MD	N/25mm	350	PSTC 131
Elongation at break	%	33	PSTC 131
Temp. Resistance	°C	60°C	=

APPLICATION

Medium strength tensilized PP film tape suitable for fixing components inside refrigerators and other household appliances in line production and during transport; removable without any adhesive residue. Euro PP 505 blue version.

Features	Benefits	
Natural rubber and resins adhesive	✓ Good adhesion in most situations ✓ Removable without residues	✓ No chemical reaction with application surfaces
Blue MOPP backing	✓ High resistance at break	✓ High security in application

CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperature are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.