

PRODUCT INFORMATION

P-1800

DESCRIPTION

High tensile palletizing single sided tape.

PRODUCT DATA

Backing	0.075 mm MOPP film; black, white, transparent
Adhesive	Synthetic rubber and resins

	Unit	Value	Method
Total thickness	mm	0.097	PSTC 133
Adhesion to steel	N/25mm	15	PSTC 101
Tensile strength MD	N/25mm	650	PSTC 131
Elongation at break	%	35	PSTC 131
Temp. Resistance	°C	60°C	=

APPLICATION

High strength tensilized PP film suitable for medium reinforcement and palletizing.

Features	Benefits	
Synthetic rubber and resins adhesive	✓ High adhesion in most situations	✓ Very sticky on several surfaces
MOPP backing	✓ High resistance at break ✓ Easy handling	✓ High security in application

CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperature are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.