

# Scotch™ brand No. 2125 Polyethylene Tape (Clear)



## Technical Data

### SCOTCH BRAND NO. 2125 POLYETHYLENE TAPE (CLEAR)

**DESCRIPTION:** A polyethylene tape with a medium-tack adhesive system designed to protect metals, plastics and painted metal panels.

**CONSTRUCTION:**

Backing:	Low-density polyethylene
Adhesive:	Acrylic
Colors:	Clear, blue*
Standard Roll Size:	48 in. (1,21 mm), 60 in. (1,52 m), 72 in. (1.82 m) x 1000 ft.(304,8 m) to 5000 ft. (1524 m)

**TYPICAL PHYSICAL PROPERTIES:** Not Recommended for Specification Purposes.

		<u>ASTM METHOD</u>
Adhesion to Steel:	5.0 oz./in. width (7 N/100 mm) nominal	<b>D-3330</b>
Tensile Strength: (Break or Yield)	2500 PSI/1.7 MPA	<b>D-882</b>
Elongation: (Break or Yield)	450%	<b>D-882</b>
Total Tape Thickness:	2.0 mils (.05 mm) nominal	<b>D-3652</b>

**GENERAL INFORMATION:**

Protective tape No.2125 is designed to offer protection for aluminum and stainless materials, painted metals and plastics with minimum adhesion buildup and clean removal. For optimum performance, Scotch brand protective tapes should be applied and removed at a room temperature not less than 60°F (16°C). Avoid prolonged exposure to UV sunlight

**POSSIBLE USES:**

- Protection of mill finish aluminum and 2b, #3 finish stainless.
- Protection of painted, embossed, architectural building panels.
- Protection of molded plastic materials.
- Protection of fine matte laminates and acrylic sheets.

\*Contact your local 3M sales representatives for additional information on colors.

# Scotch™ brand No. 2125 Polyethylene Tape (Clear)

## Page 2

### FEATURES

### ADVANTAGES

### BENEFITS

Medium-tack adhesive

Will adhere to fine matte materials without lifting

Reduces rework

Transparent backing

Allows inspection without tape Removal

Saves money on reworks

Easy punch characteristics

Withstands most forming operations where die tolerance are critical

Saves money on reworks

Acrylic Adhesive

Noncorrosive, nonstaining

Clean removal  
Reduces labor costs

---

Important Notice: User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of application.

**Warranty and Limited Remedy:** THE FOLLOWING WARRANTIES ARE MADE IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTY OF MERCHANTABILITY, THE IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE AND ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, A CUSTOM OR USAGE OF TRADE: 3M warrants its tapes will be free from defects in materials and manufacture. If a tape is proved to be defective, then the exclusive remedy and 3M's sole obligation shall be, at 3M's option, to replace the quantity of the tape which is proved to be defective or to refund the purchase price.

**Limitation of Liability:** 3M and seller shall not be liable for direct, indirect, special, incidental or consequential damages based upon breach of warranty, breach of contract, negligence, strict liability of any other legal theory.

The foregoing Warranty and Limited Remedy and Limitation of Liability may be changed only by a written agreement signed by authorized officers of 3M and seller.

70-0704-5701-8

"Scotch" is a trademark of 3M

© 3M 1992

Litho in USA with 3M offset plates, film and proofing systems.

---

## 3M Industrial Tape Division

3M Center Bldg. 220-8E-04  
St. Paul, NM 55411-1000

