



Matte White Film Tape

2185

Technical Data

Product Description 3M™ Matte White Film Tape 2185 can be used for many general masking applications requiring a white backing as it is receptive to pencil, lead and ink.

Product Construction	Backing	Adhesive	Color	Standard Roll Length
	Polypropylene film	Rubber	White with a matte finish	60 yds. (55 m)

Typical Physical Properties **Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.**

		ASTM Test Method
Adhesion to Steel:	41 oz./in. width (60 N/100 mm)	D-3330
Tensile Strength at Break:	15 lbs./in. width (237 N/100 mm)	D-3759
Elongation at Break:	25%	D-3759
Backing Thickness:	3.5 mils (0.09 mm)	D-3652
Total Tape Thickness:	4.5 mils (0.11 mm)	D-3652

Features

- Has excellent moisture and solvent resistance.
- Should not be exposed to outdoor weathering for extended periods of time.
- Special adhesive for immediate adhesion and good holding power.
- Exclusive backsize treatment for controlled unwind.

Application Ideas

- May also be used for certain other film tape applications where long yardage rolls are needed for use on automatic equipment. Rolls are supplied in both planetary and level wound rolls.
- Ideal for use as hinges and edging tape for the photo album industry. Other film tape applications such as sealing, bundling, may be evaluated.

3M™ Matte White Film Tape

2185

Product Use

All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

Warranty and Limited Remedy

Unless stated otherwise in 3M's product literature, packaging inserts or product packaging for individual products, 3M warrants that each 3M product meets the applicable specifications at the time 3M ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. 3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If the 3M product is defective within the warranty period, your exclusive remedy and 3M's and seller's sole obligation will be, at 3M's option, to replace the product or refund the purchase price.

Limitation of Liability

Except where prohibited by law, 3M and seller will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

ISO 9001:2000

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001:2000 standards.



Industrial Business Industrial Adhesives and Tapes Division

3M Center, Building 21-1W-10, 900 Bush Avenue
St. Paul, MN 55144-1000
800-362-3550 • 877-369-2923 (fax)
www.3M.com/industrial



Recycled Paper
40% pre-consumer
10% post-consumer

Printed in U.S.A.
©3M 70-0703-2613-0 (1999/5/05)