



Automotive Transit Tape

24S56

Technical Data

October, 1995

Product Description A medium-tack protective tape to help protect many painted metals and finishes

| Construction | Backing | Adhesive | Colors | Standard Roll Size |
|--------------|---------------------------------|----------|--------|--|
| | Polypropylene Multipolymer Film | Acrylic | White | 60 in. (1500 mm) and 63 in (1575 mm), × 1000 ft. (304,8 m) to 5000 ft. (1524 m) |

Typical Physical Properties and Performance Characteristics

Note: The following technical information and data should be considered representative or Typical only and should not be used for specification purposes.

| | | ASTM Test Method |
|---------------------------------------|--|------------------|
| Adhesion to Steel: | 9.0 oz./in width (8 N/100mm) normal | D-3330 |
| Tensile Strength: (Break or Yield) | Machine Direction : 5000 PSI/80 MPA Transverse Direction: 3800 PSI/62 MPA | D-882 |
| Elongation: (Break or Yield) | 700% | D-882 |
| Total Tape Thickness: | 2.0 mils (0.7 mm) nominal | D-3652 |

General Information

24S56 Transit Tape help protect many painted metals and plastics with minimum adhesion build-up and clean removal after exposure to outdoor elements. For optimum performance, this tape should be applied and removed at a temperature not less than 60°F (16°C).

Automotive Transit Tape

24S56

| Features | Advantages | Benefits |
|---|--|---|
| <ul style="list-style-type: none">• Low-Blocking Acrylic Adhesive• Repositionable Tape | <ul style="list-style-type: none">• Ease of unwind• Ease of application | <ul style="list-style-type: none">• Helps reduce labor• Helps reduce waste and labor |
| <ul style="list-style-type: none">• White Colored Backing | <ul style="list-style-type: none">• Helps reduce risks of high sunlight heat exposure | <ul style="list-style-type: none">• Ease or removability |
| <ul style="list-style-type: none">• U.V. Resistant Film Backing | <ul style="list-style-type: none">• Helps reduce risk of film degradation from U.V. exposure | <ul style="list-style-type: none">• Helps reduce rework |
| <ul style="list-style-type: none">• Abrasion Resistant Backing | <ul style="list-style-type: none">• Helps reduce damage from rail-dust, stone chips and iron filings | <ul style="list-style-type: none">• Helps reduce rework |

For Additional Information

To request additional product information or to arrange for sales assistance, call toll free 1-800-624-4772. Address correspondence to : 3M/PolyMask, 500 Thornburg Dr., P.O. Box 309, Conover, NC 28613. Our fax number is 704-465-2404 in Canada, phone: 1-519-451-2500. In Puerto Rico, phone:1-809-750-3000. in Mexico. Phone: 5-728-0400.

Important Notice

SELLER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the 3M brand product is fir for a particular purpose and suitable for user's method of application. Please remember that many factors can affect the use and performance of a 3M brand product in a particular application. The materials to be bonded with the product, the surface preparation of those materials, the product selected for use, the conditions in which the product is used, and the time and environmental conditions in which the product is expected to perform are among the many factors that can affect the use and performance of a 3M brand product. Given the variety of factors that can affect the use and performance of a 3M brand product. Some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M brand product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

Limitation of Remedies and Liability

If the 3M product is proved to be defective, THE EXCLUSIVE REMEDY, AT 3M'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE 3M PRODUCT. 3M shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.

ISO 9002

This product was manufactured by PolyMask Corporation, a joint venture of 3M and Sealed Air Corporation, and sold by 3M.

3M

Industrial Tape and Specialties Division

3M Center, Building 220-7E-01
St. Paul, MN 55144-1000

Recycled Paper
40% pre-consumer
10% post-consumer

Printed in U.S.A.
Copyright © 1999, 3M IPC. All rights reserved.
70-0706-5945-6