



# Co-Extruded Protective Tape (Clear)

## 2E79

Technical Data

March, 1995

**Product Description** A co-extruded, multi-polymer protective tape with a very high-tack adhesive system.

Construction	Backing	Adhesive	Colors	Standard Roll Size
	Multi-polymer*	Acrylic	Clear	60 in. (1500 mm), 63 in. (1575) x 1000 ft. (304,8 m) to 3000 ft. (914,4 m)

\*Resins used in the construction of the film backing are proprietary.

### Typical Physical Properties and Performance Characteristics

**Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.**

		ASTM Test Method
Adhesion to Steel:	20.0 oz./in. width (20 N/100 mm) nominal	D-3330
Tensile Strength: (Break)	4500 PSI/3.1 MPA	D-882, D-3759
Elongation: (Break)	600%	D-882, D-3759
Total Tape Thickness:	2.0 mils (.05 mm) nominal	D-3652

### General Information

- 2E79 Protective tape is designed for many automotive carpet applications. For optimum performance, 3M™ protective tapes should be applied and removed at a temperature not less than 60°F (16°C).

**Note:** Avoid prolonged exposure to UV sunlight.

### Application Ideas

Protection of...

- Automotive Carpeted Floors
- Fabric Seats and Headliners

# 3M™ Co-Extruded Protective Tape (Clear)

2E79

Features	Advantages	Benefits
<ul style="list-style-type: none"><li>• High-tack adhesive</li></ul>	<ul style="list-style-type: none"><li>• Will adhere to many matte textured materials</li></ul>	<ul style="list-style-type: none"><li>• Helps reduce rework</li></ul>
<ul style="list-style-type: none"><li>• High-coating weight</li></ul>	<ul style="list-style-type: none"><li>• Will wet out most surfaces with low contact area</li></ul>	<ul style="list-style-type: none"><li>• Helps reduce rework</li></ul>
<ul style="list-style-type: none"><li>• Enhanced conformability</li></ul>	<ul style="list-style-type: none"><li>• Conforms to many products with irregular, textured surfaces</li></ul>	<ul style="list-style-type: none"><li>• Helps reduce rework</li></ul>

---

## Important Notice

SELLER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the 3M brand product is fit for a particular purpose and suitable for user's method of application. Please remember that many factors can affect the use and performance of a 3M brand product in a particular application. The materials to be bonded with the product, the surface preparation of those materials, the product selected for use, the conditions in which the product is used, and the time and environmental conditions in which the product is expected to perform are among the many factors that can affect the use and performance of a 3M brand product. Given the variety of factors that can affect the use and performance of a 3M brand product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M brand product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

---

## Limitation of Remedies and Liability

If the 3M brand product is proved to be defective, THE EXCLUSIVE REMEDY, AT SELLER'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE 3M BRAND PRODUCT. Seller shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.

**This product is manufactured by PolyMask Corporation, a joint venture of 3M and Sealed Air Corporation, and sold by 3M.**



Industrial Tape and Specialties Division

3M Center, Building 220-7E-01  
St. Paul, MN 55144-1000



Recycled Paper  
40% pre-consumer  
10% post-consumer

Printed in U.S.A.  
©3M 1994 70-0704-5968-3