Technical Information

Scotch[™]brand No. 3173 Polyethylene Tape (Clear)



Technical Data

SCOTCH BRAND NO. 3173 POLYETHYLENE TAPE (CLEAR)

DESCRIPTION: A polyethylene tape with a low-tack adhesive system designed to protect vinyl

CONSTRUCTION:

Backing:	Low-density polyethylene
Adhesive:	Acrylic
Colors:	Clear*
Standard Roll Size:	48 in. (1,21 mm), 60 in. (1,52 m), 72 in. (1.82 m) x 1000 ft.(304,8 m) to 5000 ft. (1524 m)

TYPICAL PHYSICAL PROPERTIES: Not Recommended for Specification Purposes.

ASTM METHOD

Adhesion to Steel:	3.5 oz./in. width (4 N/100 mm) nominal	D-3330
Tensile Strength: (Break or Yield)	2500 PSI/1.7 MPA	D-882
Elongation:	450%	D-882
(Break or Yield) Total Tape Thickness:	3.0 mils (.07 mm) nominal	D-3652

GENERAL INFORMATION:

Protective tape No.3173 is constructed of a proprietary adhesive system specifically designed to be used as a vinyl premask. For optimum performance, Scotch brand protective tapes should be applied and removed at a room not less than $60^{\circ}F(16^{\circ}C)$. Avoid prolonged exposure to UV sunlight.

POSSIBLE USES:

For application as a premask for vinyl pinstriping, decals and lettering.

*Contact your local 3M sales representatives for additional information on colors.

Scotch[™]brand No. 3173 Polyethylene Tape (Clear) Page 2

FEATURES	ADVANTAGES	<u>BENEFITS</u>
Transparent backing	Allows inspection without tape Removal	Saves money on reworks
Elastic backing	Excellent conformability for hand applications with a severe radius	Saves money on time and reworks
Proprietary adhesive	Specifically designed for compatibility with vinyls	Universal compatibility with a variety of substrates
Low-tack adhesive	Minimal adhesion buildup easy removal	Reduces labor costs

Important Notice: User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of application.

Warranty and Limited Remedy: THE FOLLOWING WARRANTIES ARE MADE IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR INPLIED. INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTY OF MERCHANTABILITY, THE IMPLIED WARRANTY OF FITNESS FOR A PARRICULAR PURPOSE AND ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF EDALING. A CUSTOM OR USAGE OF TRADE:3M warrants its tapes will be free from detects in materials and manufacture. If a tape is proved to be defective, then the exclusive remedy and 3M's sole obligation shall be, at 3M's option, to replace the quantity of the tape which is proved to be defective or to refund the purchase price.

Limitation of Liability:3M and seller shall not be liable for direct, indirect, special, incidental or consequential damages based upon breach of warranty, breach of contract, negligence, strict liability of any other legal theory.

The foregoing Warranty and Limited Remedy and Limitation of Liability may be changed only by a written agreement signed by authorized officers of 3M and seller.

70-0704-5718-2

© 3M 1992

Litho in USA with 3M offset plates, film and proofing systems.

3M Industrial Tape Division

"Scotch" is a trademark of 3M

3M Center Bldg. 220-8E-04 St. Paul. NM 55411-1000

