# **Technical Information**

# Scotch<sup>™</sup> brand No. 365 Thermosetting Glass Cloth Tape



### **Technical Data**

#### SCOTCH BRAND NO. 365 THERMOSETTING GLASS CLOTH TAPE

A Thermosetting adhesive, glass cloth tape, designed for applications requiring high **DESCRIPTION:** adhesion and a very strong backing.

#### **CONSTRUCTION:**

Backing:	Glass, Cloth
Adhesive:	Thermosetting rubber
Color:	White
Standard Roll Length:	60 yards (55 m)
L PHYSICAL PROPERTIES:	Not Recommended for Specification Purposes

**TYPICAL PHYSICAL PROPERTIES:** 

**ASTM METHOD** 

Adhesion to Steel:	60 oz./in. width (54.5 N/100mm)	D-3330
Tensile at Break: (Bleak)	106 lbs./in. width (2106 N/ 100mm)	D-3759
Backing Thickness:	5 mils. (.12 mm)	D-3652
Total Tape Thickness:	7.2 mils (.18mm)	D-3652

#### **GENERAL INFORMATION:**

- 1. This adhesive provides good initial adhesion and tack. When subjected to a thermosetting cycle it will crosslink, providing greater adhesion and bonding, high solvent resistance and higher heat resistance.
- 2. Thermosetting is frequently achieved by ironing the backing once the tape is applied Specific high adhesion is obtained by optimizing the time, pressure, and temperature of the heat application

#### **POSSIBLE USES:**

Splicing or insulation applications requiring high tensile strength and resistance to elevated temperatures.

As a corrosion resistant wrap on stainless steel hot air ducts.

Splicing materials with rough surfaces of poor internal strength such as roofing felt of fiberglass.

# Scotch<sup>™</sup> brand No. 365 Thermosetting Glass Cloth Tape Page 2

<b>FEATURES</b>	<b>ADVANTAGES</b>	<b>BENEFITS</b>
	Excellent heat and solvent resistance	High productivity
	High tensile strength	Withstands high temperatures
	Will not shrink, rot or burn	
Adhesive	Firm at high temperature	High productivity
	Good solvent resistance	Produces excellent bond

Important Notice: All statements, technical information and recommendations herein are based on tests and data we believe to reliable, But the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties. expressed or implied, including the implied warranties of merchantability and fitness for purpose. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith. NEITHER SELLER NOR MANUFACTURER SHALL BE LIABLE EITHER IN TORT OR IN CONTRACT FOR ANY LOSS OR DAMAGE, DIRECT, INCIDENTAL, OR CONSEQUENTIAL, ARISING OUT OF THE USE OF OR THE INABILITY TO USE THE PRODUCT. No statement or recommendation not contained herein shall have any force of effect unless in an agreement signed by officers of seller and manufacturer.

70-0703-2861-5

"Scotch" is a trademark of 3M

© 3M 1989

Litho in USA with 3M offset plates, film and proofing systems.

## **3M Industrial Tape Division**

3M Center Bldg. 220-8E-04 St. Paul. NM 55411-1000

