

Technical Information

370



Highland™ Industrial Box Sealing Tape

1. :

 :
 :
 :
 : , Polypropylene(BOPP) film.

2.

 :
 :
 :
 : 36mm, 48mm, 72mm
 : 50M , 100M, 200M, 914M, 1000M, 1500M
 (ID) : 3 inch

3. (not recommended for specification purposes)

(Adhesion to Steel):	1134 g/in. width	ASTM D-3330
(Tensile Strength) :		
Machine Direction	9.5 Kg/in. width	ASTM D-3759
Cutting Direction	19 Kg./in. width	ASTM D-3759
(Thickness) :		
(Backing) :	0.028 mm	ASTM D-3652
(Total) :	0.048 mm	ASTM D-3652

4.

 , 4 - 26 °C 40 - 50 %RH

1

5.

Technical Data: All physical properties, statements, and recommendations are either based on tests we believe to be reliable or our experience, but they are not guaranteed. 3M recommends each user determine the suitability of the tape for the intended use.

Warranty and Limited Remedy: THE FOLLOWING WARRANTY IS MADE IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTY OF MERCHANTABILITY, THE IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE AND ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, A CUSTOM OR USAGE OF TRADE:

3M warrants its tapes will be free from all defects in materials and manufacture. If tape is proved to be defective, then the exclusive remedy and 3M's and seller's sole obligation shall be, at 3M's option, to replace the quantity of the product which is proved to be defective or to refund the purchase price.

Limitation of Liability: 3M and seller shall not be liable for direct, indirect, special, incidental or consequential damages based upon breach of warranty, breach of contract, negligence, strict liability or any other legal theory.

The foregoing Warranty and Limited Remedy and Limitation of Liability may be changed only by a written agreement signed by authorized officers of 3M and seller .