

# Scotch™ brand No. 3W26 Outdoor Polyethylene Tape (Black/White)



## Technical Data

### SHOTCH BRAND NO. 3W26 OUTDOOR POLYETHYLENE TAPE (BLACK/WHITE)

**DESCRIPTION:** A co-extruded polyethylene tape with a medium-tack adhesive system specifically designed for outdoor and indoor protection of metals, plastics and glass.

### CONSTRUCTION:

Backing:	Co-extruded low-density polyethylene
Adhesive:	Acrylic
Colors:	White (outside layer) Black (inside layer)
Standard Roll Size:	48 in. (1,21 mm), 60 in. (1,52 m) × 1000 ft.(304,8 m) to 5000 ft. (1524 m)

**TYPICAL PHYSICAL PROPERTIES:** Not Recommended for Specification Purposes.

		<u>ASTM METHOD</u>
Adhesion to Steel:	7.0 oz./in. width (3 N/100mm) nominal	<b>D-3330</b>
Tensile Strength: (Break or Yield)	2500 PSI/1.7 MPA	<b>D-882</b>
Elongation: (Break or Yield)	450%	<b>D-882</b>
Total Tape Thickness:	3.0 mils (.08 mm) nominal	<b>D-3652</b>

### GENERAL INFORMATION:

Protective tape No.3W26 is designed to protect mill-finished stainless and aluminum and low-gloss painted metals and plastics with minimum adhesion buildup and clean removal after exposure to outdoor environments. For optimum performance, Scotch brand protective tapes should be applied and removed at a room temperature not less than 60°F (16°C).

### POSSIBLE USES:

An outdoor protective tape designed for finished stainless and aluminum sheets and coils in fabrication, shipping and storage.

Protection of automotive paint finishes from damage caused by exposure to acid rain.

# Scotch™ brand No. 3W26 Polyethylene Tape (Black/White)

## Page 2

### FEATURES

Black/white film

Superior UV resistance

Medium-tack adhesive

Low-blocking acrylic adhesive

Abrasion-resistant backing

### ADVANTAGES

Reduces risk of exposure to UV

Will not lift after exposure to heat and pressure

Easy unwind facilitates productivity at application

Resists tearing at forming

### BENEFITS

No adhesive residue reducing labor costs

Reduces rework

Reduces labor costs

Reduces reworks, rejects and scrap

---

Important Notice: User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of application.

**Warranty and Limited Remedy:** THE FOLLOWING WARRANTIES ARE MADE IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED. INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTY OF MERCHANTABILITY, THE IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE AND ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING. A CUSTOM OR USAGE OF TRADE: 3M warrants its tapes will be free from defects in materials and manufacture. If a tape is proved to be defective, then the exclusive remedy and 3M's sole obligation shall be, at 3M's option, to replace the quantity of the tape which is proved to be defective or to refund the purchase price.

**Limitation of Liability:** 3M and seller shall not be liable for direct, indirect, special, incidental or consequential damages based upon breach of warranty, breach of contract, negligence, strict liability of any other legal theory.

The foregoing Warranty and Limited Remedy and Limitation of Liability may be changed only by a written agreement signed by authorized officers of 3M and seller.

70-0704-3043-7

"Scotch" is a trademark of 3M

© 3M 1989

Litho in USA with 3M offset plates, film and proofing systems.

---

## 3M Industrial Tape Division

3M Center Bldg. 220-8E-04  
St. Paul, NM 55411-1000

