

Scotch™ brand No. 4126 Polyethylene Tape (Clear)



Technical Data

SCOTCH BRAND NO. 4126 POLYETHYLENE TAPE (CLEAR)

DESCRIPTION: A polyethylene tape with a medium-tack adhesive system, designed to specifically offer enhanced surface protection for metals, painted metals, plastics and fiberglass materials.

CONSTRUCTION:

Backing:	Low-density polyethylene
Adhesive:	Acrylic
Colors:	Clear *
Standard Roll Size:	48 in. (1,21 mm), 60 in. (1,52 m), 72 in. (1.82 m)x 1000 ft.(304,8 m) to 3000 ft. (914,4 m)

TYPICAL PHYSICAL PROPERTIES: Not Recommended for Specification Purposes.

		<u>ASTM METHOD</u>
Adhesion to Steel:	7.0 oz./in. width (7 N/100mm) nominal	D-3330
Tensile Strength: (Break or Yield)	2500 PSI/1.7 MPA	D-882
Elongation: (Break or Yield)	450%	D-882
Total Tape Thickness:	4.0 mils (.10 mm) nominal	D-3652

GENERAL INFORMATION:

Protective tape No.4126 is designed to offer increased surface protection for slightly textured metals, painted metals and plastics that are subjected to forming operations such as roll forming, stamping and die cutting. For optimum performance, Scotch brand protective tapes should be applied and removed at a room temperature not less than 60°F (16°C). This product is not designed for prolonged exposure to direct sunlight for extended periods.

POSSIBLE USES:

Protection of polished #3 and #4 finished stainless coils or sheets.
Protection of painted, flat-finish building panels.
Protection of molded fiberglass or acrylic tubs and spas.
Automotive applications include protection of bumpers and fascias, body side molding, paint protection and tail lights or window glass.

*Contact your local 3M sales representatives for additional information on colors.

Scotch™ brand No. 3W26 Polyethylene Tape (Black/White)

Page 2

<u>FEATURES</u>	<u>ADVANTAGES</u>	<u>BENEFITS</u>
Low-tack adhesive	Will adhere to textured materials	Reduces labor costs
4 mil backing	Increases surface protection	Saves money on rework, Rejects and scrap
Transparent backing	Allows inspection without tape Removal	Save money on reworks
Elastic backing	Resist tearing and withstands Most forming operations	Save money on reworks
Acrylic adhesive	Nonstaining /noncorrosive	Clean removal, Saves money on reworks
Humidity-resistant adhesive	Minimizes risk of residue when Used in environments with high Humidity	Clean removal, reduces labor costs

Important Notice: User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of application.

Warranty and Limited Remedy: THE FOLLOWING WARRANTIES ARE MADE IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTY OF MERCHANTABILITY, THE IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE AND ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING. A CUSTOM OR USAGE OF TRADE: 3M warrants its tapes will be free from defects in materials and manufacture. If a tape is proved to be defective, then the exclusive remedy and 3M's sole obligation shall be, at 3M's option, to replace the quantity of the tape which is proved to be defective or to refund the purchase price.

Limitation of Liability: 3M and seller shall not be liable for direct, indirect, special, incidental or consequential damages based upon breach of warranty, breach of contract, negligence, strict liability of any other legal theory.

The foregoing Warranty and Limited Remedy and Limitation of Liability may be changed only by a written agreement signed by authorized officers of 3M and seller.

70-0704-5708-3

"Scotch" is a trademark of 3M

© 3M 1992

Litho in USA with 3M offset plates, film and proofing systems.

3M Industrial Tape Division

3M Center Bldg. 220-8E-04
St. Paul, NM 55411-1000

