

# Scotch™ brand No. 5112 Polyethylene Tape (Clear)



## Technical Data

### SCOTCH BRAND NO. 5112 POLYETHYLENE TAPE (CLEAR)

**DESCRIPTION:** A polyethylene tape with a low-tack adhesive system designed to maximize surface protection for polished metals, plastics and glass materials.

### CONSTRUCTION:

Backing:	Low-density polyethylene
Adhesive:	Natural rubber latex emulsion (proprietary)
Colors:	Clear*
Standard Roll Size:	48 in. (1,21 mm), 60 in. (1,52 m), 72 in. (1.82 m)x 1000 ft.(304,8 m) to 3000 ft. (914,4 m)

**TYPICAL PHYSICAL PROPERTIES:** Not Recommended for Specification Purposes.

		<u>ASTM METHOD</u>
Adhesion to Steel:	3.0oz./in. width (2 /100mm) nominal	<b>D-3330</b>
Tensile Strength: (Break or Yield)	2500 PSI/1.7 MPA	<b>D-882</b>
Elongation: (Break or Yield)	450%	<b>D-882</b>
Total Tape Thickness:	50 mils (.13mm) nominal	<b>D-3652</b>

### GENERAL INFORMATION:

Protective tape No.5112 is designed to offer greater protection for, material surfaces that are susceptible to damage caused by abrasion and marring. For optimum performance, Scotch brand protective tapes should be applied and removed at a room temperature not less than 60°F(16°C). This product is not designed for prolonged exposure to direct sunlight for extended periods.

### POSSIBLE USES:

Protection of mirror-finish stainless, specular anodized aluminum.

Protection of painted, gloss-finish, metal building panels.

Automotive applications include protection from paint mutilization, tail lights, lens covers and window glass.

\*Contact your local 3M sales representatives for additional information on colors.

# Scotch™ brand No. 5112 Polyethylene Tape (Clear)

## Page 2

### FEATURES

Low-tack adhesive

5 mil backing

Transparent backing

Minimal adhesion buildup

### ADVANTAGES

Easy removal

Enhances abrasion resistance

Allows inspection without tape  
Removal

Easy release

### BENEFITS

Reduces labor costs

Reduce reworks  
Increases surface protection

Reduces reworks

Reduces labor costs

---

Important Notice: User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of application.

**Warranty and Limited Remedy:** THE FOLLOWING WARRANTIES ARE MADE IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTY OF MERCHANTABILITY, THE IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE AND ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, A CUSTOM OR USAGE OF TRADE: 3M warrants its tapes will be free from defects in materials and manufacture. If a tape is proved to be defective, then the exclusive remedy and 3M's sole obligation shall be, at 3M's option, to replace the quantity of the tape which is proved to be defective or to refund the purchase price.

**Limitation of Liability:** 3M and seller shall not be liable for direct, indirect, special, incidental or consequential damages based upon breach of warranty, breach of contract, negligence, strict liability of any other legal theory.

The foregoing Warranty and Limited Remedy and Limitation of Liability may be changed only by a written agreement signed by authorized officers of 3M and seller.

70-0704-3041-1

"Scotch" is a trademark of 3M

© 3M 1992

Litho in USA with 3M offset plates, film and proofing systems.

---

## 3M Industrial Tape Division

3M Center Bldg. 220-8E-04  
St. Paul, NM 55411-1000

