Scotch[™]brand No.5187 Polyethylene Tape (Clear)



Technical Data

SCOTCH BRAND NO. 5187 POLYETHYLENE TAPE (CLEAR)

DESCRIPTION: A polyethylene tape with a high-tack adhesive system designed to offer maximum

abrasion resistance for textured metals and fine matte plastic materials.

CONSTRUCTION:

Backing: Low-density polyethylene

Adhesive: Acrylic Colors: Clear*

Standard Roll Size: 48 in. (1,21 mm), 60 in. (1,52 m), 72 in. (1.82 m)x

1000 ft.(304,8 m) to 3000 ft. (914,4 m)

TYPICAL PHYSICAL PROPERTIES: Not Recommended for Specification Purposes.

ASTM METHOD

Adhesion to Steel: 13 oz./in. width (12 N/100 mm) nominal **D-3330**Tensile Strength: 2500 PSI/1.7 MPA **D-882**

(Break or Yield)

Elongation: 450% **D-882**

(Break or Yield)

Total Tape Thickness: 5.0 mils (.13 mm) nominal **D-3652**

GENERAL INFORMATION:

Protective tape No.5187 is designed to provide maximum surface protection for metals and plastic materials with a coarse textured surface. For optimum performance, Scotch brand protective tapes should be applied and removed at a room temperature not less than $60^{\circ}F(16^{\circ}C)$. This product is not designed for prolonged exposure to direct sunlight for extended periods.

POSSIBLE USES:

Protection of cultured marble.

Protection of lightly brushed aluminum and stainless.

Protection of fine matte high pressure laminates.

Protection of textured plastics.

Should avoid prolonged exposure to water which may increase chances of adhesive residue.

^{*}Contact your local 3M sales representatives for additional information on colors.

Scotch[™]brand No. 5187 Polyethylene Tape (Clear) Page 2

<u>FEATURES</u>	<u>ADVANTAGES</u>	BENEFITS
High-tack adhesive	Will not lift from granular Surfaces	Reduces labor costs
Transparent backing	Allows inspection without tape Removal	Reduces reworks
5 mil backing	Increased abrasion resistance	Reduces reworks surface Increases protection
Elastic backing	Withstands most forming Operations	Save money on reworks

Important Notice: User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of application.

Warranty and Limited Remedy: THE FOLLOWING WARRANTIES ARE MADE IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR INPLIED. INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTY OF MERCHANTABILITY, THE IMPLIED WARRANTY OF FITNESS FOR A PARRICULAR PURPOSE AND ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF EDALING. A CUSTOM OR USAGE OF TRADE:3M warrants its tapes will be free from detects in materials and manufacture. If a tape is proved to be defective, then the exclusive remedy and 3M's sole obligation shall be, at 3M's option, to replace the quantity of the tape which is proved to be defective or to refund the purchase price.

Limitation of Liability:3M and seller shall not be liable for direct, indirect, special, incidental or consequential damages based upon breach of warranty, breach of contract, negligence, strict liability of any other legal theory.

The foregoing Warranty and Limited Remedy and Limitation of Liability may be changed only by a written agreement signed by authorized officers of 3M and seller.

70-0704-3048-6 "Scotch" is a trademark of 3M © 3M 1992 Litho in USA with 3M offset plates, film and proofing systems.

3M Industrial Tape Division

3M Center Bldg. 220-8E-04 St. Paul. NM 55411-1000

