



Tear Strip Tape

8612

Technical Information Revision 1

A high-performance translucent tape reinforced with continuous polyester filaments. Scotch® Tear Strip Tape 8612 is designed as an easy-opening tear strip tape for single-wall corrugated containers.

Construction

Backing:	Scotchpar™ film
Adhesive:	Pressure sensitive rubber resin
Reinforcement:	Polyester yarn
Backing Color:	Clear

Typical Physical Properties (Not recommended for specification purposes)

		<u>ASTM Test Method</u>
Roll Diameter	13 inch (330 mm)	
Adhesion to Steel:	4.1 oz/tape width (1.14 N/tape width)	D-3330
Tensile Strength:	40 lb/tape width (178 N/tape width)	D-3759
Elongation at Break:	15%	D-3759

Available Widths

Available Lengths

Standard widths:	3/16 inch (4.8 mm)	12000 yards (10970 m)
Core size (ID):	6 inch (152.4 mm)	

Storage Conditions

Store behind present stock. Store in a clean dry place. Temperature of 40-80 °F (4-26 °C) and 40-50% relative humidity are recommended. Rotate your stock.

Scotch® Tear Strip Tape 8612 is produced in an ISO 9002 registered manufacturing facility

Technical Data: All physical properties, statements, and recommendations are based either on tests we believe to be reliable or our experience, but they are not guaranteed. 3M recommends each user determine the suitability of the product for the intended use.

Warranty and Limited Remedy: THE FOLLOWING WARRANTY IS MADE IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE:

3M warrants its tapes will be free from defects in material and manufacture. If a tape is proved to be defective, then the exclusive remedy, and 3M's and seller's sole obligation shall be, at 3M's option, to replace the quantity of the tape which is proved to be defective or to refund the purchase price.

Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from this 3M product, whether direct, indirect, special, incidental or consequential regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

The foregoing Warranty and Limited Remedy and Limitation of Liability may be changed only by a written agreement signed by authorized officers of 3M and seller.

3M Packaging Systems Division

3M Center, Building 230-1E-04
St. Paul, MN 55144-1000 USA
1- 800-722-5463

Printed in U.S.A.
© 3M 2000